



CROSS 60 DIRECT FLOW REVERSE OSMOSIS FILTER



KEY FEATURES

- Direct flow rate: 1 L/min
- 50% recovery rate: efficient water saving technology
- DIY filter change: easy cartridge replacement in 10 minutes
- Slim Design: save more under sink space
- Basic model: minimal smart features for easy use

FILTRATION TECHNOLOGY:

- Composite PP and carbon block filter — removes sediment impurities such as sand, silt, and rust. Also reduces chlorine, organic matter, and organochlorine compounds.
- Membrane element 400 GPD — removes up to 99.8% of impurities, including bacteria, viruses, and PFAS. Ideal for high water consumption needs.
- Carbon block postfilter — enhances the taste and odor of purified water.

SPECIFICATION:

Code	Description	Direct flow rate, L/h	Recovery, %	Inlet water pressure, bar	Electrical, V, 50 Hz	Dimensions, H x W x D, mm	Pieces on pallet
MO3400PECO	CROSS 60 direct flow reverse osmosis filter	60	50	2-5	230	435 x 140 x 458	18



REPLACEMENT CARTRIDGES:

Code	Description	Replacement/ months	Pieces in box	Boxes on pallet
CPVDFRO	CF complex prefilter	12		
CSVRO400DFRO	400 GPD membrane element	24	6	96
CHVCBDFRO	CB carbon block postfilter	12	12	192

Make sure to install a pressure reducer before the filter!

We recommend discarding the first two glasses of water in the morning or using them to water plants. Due to natural diffusion during overnight downtime, the quality of the purified water may deteriorate.